

# H3C086 Li-Ion Charger 40 W

- Ideally suited to charge Li-Ion battery packs with 4 cells in series
- Complies with medical standard (EN60601)
- UL approved (UL-2601-1)
- Low ripple noise
- Mains cord not included
- 1 year warranty



## Model selection guide

| Typ    | Input nominal voltage [V <sub>AC</sub> ] | Input current full-load [mA] | Output voltage [V <sub>DC</sub> ] | Output current [mA] |
|--------|--|------------------------------|-----------------------------------|---------------------|
| H3C086 | 85 – 264                                 | 300                          | 16.4                              | 2000                |

## Specifications

|                    |   |
|--------------------|---|
| <b>Input</b>       |   |
| Voltage range      | AC 85 V – 264 V<br>Universal full range |
| Input frequency    | 47 – 63 Hz                              |
| Current            | 300 mA RMS max.                         |
| <b>Others</b>      |   |
| Cooling            | Natural Cooling                         |
| Dimensions         | 107x67x36,5mm                           |
| Weight             | 250 g                                   |
| <b>Environment</b> |   |
| Temperature range  | -10°C – + 40°C                          |

|                  |   |
|------------------|---|
| <b>Packaging</b> | white folding box                                   |
| <b>Safety</b>    | EN60601-1, EN 60950,<br>EN60335-2-29, UL-<br>2601-1 |
| <b>EMC</b>       | EN60601-1-2,<br>EN61000-6-3,<br>EN61000-6-1         |