

PRELIMINARY

WE310K6

Wi-Fi 802.11 a/b/g/n/ac/ax

Bluetooth® | Bluetooth® Low Energy 5.2



Product Description

The WE310K6 is a fully integrated dual band, dual stream (2x2) combo Wi-Fi (802.11 a/b/g/n/ac/ax) / Bluetooth® / Bluetooth® Low Energy 5.2 module, that provides an easy, cost-effective way for manufacturers to add wireless connectivity to their products.

The WE310K6 is an ideal solution for organizations with limited Wi-Fi/Bluetooth® Low Energy or RF expertise or for those seeking faster time to market, as it reduces RF design time and removes the burden of testing and certification.

The Module is IEEE 802.11 a/b/g/n/ac/ax & Bluetooth® certified and comply with Wi-Fi Alliance & BT SIG-v5.2 requirements.

The WE310K6 module is easily designed into embedded systems, allowing customers to develop a broad array of devices and appliances that connect to other local devices or to the Internet over Wi-Fi.

Finally, the WE310K6-P is available in LGA package or on top of a M.2 Key E carrier board for an effortless integration.

Key Features

- Dual-band (2.4GHz/5GHz) Wi-Fi and Bluetooth® Low Energy combo module, 2x2, MU-MIMO
- Dual-stream spatial multiplexing up to 1201 Mbps data rate
- Dual mode Bluetooth® & Bluetooth® Low Energy – Bluetooth® 5.2
- Bluetooth® AUDIO Isochronous Channel (CIS) support
- Wi-Fi 802.11 e, h, k, i
- Advanced security features (including WPA3) with integrated crypto hardware
- Industrial grade temperature range (-40 °C to +85 °C)
- Certified Module
- Two Form Factor: LGA and M.2

Target Applications

Smart Home

- Home Automation
- Home Appliances
- Home Security and Alarm
- IP Cameras/Speakers
- Smart Lighting

Industrial and commercial

- Industrial Automation
- Energy Management
- Robotics
- Building Automation
- Smart City

Health Care & Medical

- Remote Patient Monitoring
- Healthcare Devices
- Wellness Devices
- Pet/Animal Trackers
- Medical Wearables

Others Applications

- Aftermarket OEM Telematics
- Fleet management
- Smart parking
- Printers
- Asset management

AVAILABLE FOR

North America

EMEA

Japan*

Taiwan*

China*

Korea*

Brazil*



WE310K6

WLAN Specification	Wi-Fi - 802.11 a/b/g/n/ac/ax (2.4GHz, 5GHz) 20MHz, 40MHz, 80MHz
Bluetooth® Specification	SIG v5.2 Compliant Bluetooth® 2.1 + EDR, Bluetooth® Low Energy 5.2 (simultaneous dual mode) Bluetooth® Low Energy 2Mbps, LE LR Bluetooth® Low Energy Audio (CIS)
Solution Architecture	Linux Companion
Host Interface	Wi-Fi: PCIe 1.1 Bluetooth®: HS-UART Bluetooth® Audio: PCM
Wi-Fi Modes	Wi-Fi AP (Access Point) STA (Client) Wi-Fi (AP + STA) Concurrent Mode
Peripherals	Bluetooth® Wake Host, Host Wake Bluetooth®, Host Wake WL Disable Bluetooth®, Disable WL Status: Led Bluetooth®, Led WL
Security Features	WPA/WPA2 (personal) WPA3 (personal/enterprise)*
Coexistence	Inbuilt Wi-Fi Bluetooth® Low Energy
Antenna	2 RF Pads
Dimension	LGA package, External antenna: 18 x 15 x 2.6 mm M.2 Key E: 22 x 30 x 3.4 mm
Wi-Fi Tx output power	19 dBm @ 2.4 GHz (preliminary) 18 dBm @ 5 GHz (preliminary)
BLE Tx output power	4 dBm (preliminary)
Operating Temperature	-40 °C to +85 °C (industrial grade)
Operating Voltage	3.3 V Typ
Compliance	RED/FCC/ISED/UKCA Wi-Fi Alliance Bluetooth®-SIG
Environmental Compliance	RoHS, REACH

QUESTIONS? VISIT WWW.TELIT.COM/CONTACT-US

 Like Us on Facebook
  Follow Us on LinkedIn
  Follow Us on Twitter
  Subscribe to Our Channel